

H-version Oven 32" WIDE CONVEYOR 80" LONG BAKE CHAMBER

## <u>GAS</u>

### GAS OVEN

HEATING VALUES

STANDARD BTU/Hr: 235,000 
 WORLD

 Natural:
 67.08 Kw/Hr

 241.49 Mj/Hr

 Propane:
 69.25 Kw/Hr

 249.30 Mj/Hr

 Butane:
 73.85 Kw/Hr

#### **ELECTRICAL REQUIREMENT**

STANDARD	WORLD
120 VAC, 8.5 Amps	220/230/240 VAC Option
50/60 Hz	7 Amps, 50/60 Hz

#### **INLET PRESSURE RANGE**

NATURAL G	iAS	<b>PROPANE</b>	GAS
W/C:	6-14	W/C:	11.5-14
mbar:	15-35	mbar:	27.5-35
kPa:	1.50-3.50	kPa:	2.75-3.50
kPa (Korea)	1.50-2.50	kPa (Korea):	:2.30-3.30

#### MANIFOLD PRESSURE RANGE

NATURAL GAS	<b>PROPANE GAS</b>
W/C: 3.5	W/C: 10
mbar: 8.75	mbar: 25
kPa: 0.875	kPa: 2.50


#### WEIGHT

Single: 1347 lbs/611 kg Double: 2455 lbs/1113 kg Triple: 3519 lbs/1596 kg

## WARRANTY

USA & CANADA 7 YEARS INTERNATIONAL 5 YEARS


**(()** 





FRONT VIEWS


ST.DELI


SIDE VIEWS














# WWW.XLTOVENS.COM

\*A MINIMUM OF A  $1\%^\prime\prime$  Gas supply line is required. The gas line must be placed to the side of the oven and cannot be behind the control box.

24/7/365 LIVE TECHNICAL SUPPORT

service@xltovens.com

sales@xitovens.com

Intertel